

Technical Data Sheet

HW120A General Wax Ribbons



- Lower Energy
- Darker Image
- Fine Definition
- Higher Durability
- Substantial saving

Recommended Substrates:

Rough paper
Plain paper
Coated paper
Retail tag
Synthetic paper
PE
BOPP

Specific Features:

Wide range of substrates
High blackness
High sensitivity
Fine definition
Low temperature
Protect print head

Application Fields:

Inventory
Shipping
Pharmaceutical
Retail labelling
Tags
Conveyor sorting

HW120A General purpose wax barcode ribbon which gives excellent performance on a wide variety of labels. This common wax designed to operate at low energy, high speed, and the high sensitivity ink gives excellent print density and definition.

Suitable for most Flat Head printer such as Argox, Citizen, Datamax, Intermec, Postek, Ring, Sato, Toshiba TEC Flat Head range, TSC and Zebra

Ribbon property:

Description	Specification
Ink material	Resin enhanced wax
Ink melting point	68°C
Total Thickness	7.8±0.5µm
Base film thickness	4.5±0.3µm
Ink thickness	3.3±0.3µm
Print density(Reflection)	≥1.8
Print speed	2-8IPS
Static	<3KV



Jl. Logistik No.53
Tugu Selatan – Jakarta 14260
Indonesia
info@idtech-tt.com
www.idtech-tt.com